

MATERIAL SAFETY DATA SHEET

Page 1

EFFECTIVE DATE: 04/21/06

SUPERCEDES: 12/01/05

MANUFACTURED FOR: PACIFIC PRODUX, INC
9879 HIBERT ST. STE . E
SAN DIEGO, CA 92131
(858)549-9677

CHEMTREC: 1-800-424-9300

0=Minimal

SECTION 1: GENERAL INFORMATION

PRODUCT NAME: Diamond S Dressing

PRODUCT ID: DP245

NFPA 704

HAZARD RATING

4=Severe H=1

3=Serious F=2

2=Moderate R=0

1=Slight

SECTION 1A: D.O.T. SHIPPING INFORMATION

Proper Shipping Name: NON-REGULATED MATERIAL

Hazard Class: N/A

UN/NA: N/A

Packaging Group: N/A

NOTE: N/A = NOT APPLICABLE

EMERGENCY OVERVIEW

WARNING! Combustible liquid. May cause eye and skin irritation. High concentrations of mist/aerosol may irritate the respiratory tract. Avoid contact with eye and skin. Avoid breathing vapor or mist. Do not ingest. Wash thoroughly after handling.

SECTION 2: HAZARDOUS INGREDIENTS

#	INGREDIENT	CAS #	OSHA PEL (ppm or *mg.M ³) +=skin, c=ceiling	ACGIH TLV (ppm or *mg/M ³) +=skin, c=ceiling	WEIGHT %
1	Synthetic Isoparaffinic Hydrocarbon	64742-47-8	N/A	N/A	50-80

SECTION 5: FIRE AND EXPLOSION DATA

FLASH POINT: >177F TEST: PMCC ASTM D93 (minimum)
EXPLOSIVE LIMITS: LEL: 0.5 UEL: 4.9 based upon Synthetic Isoparaffinic Hydrocarbon

EXTINGUISHING MEDIA: Use water spray, dry chemical, CO2 or "alcohol" foam.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid. Can form combustible mixtures at temperatures at or above the flashpoint. Can accumulate static charges which can cause an incendiary electrical discharge.

SPECIAL FIRE FIGHTING PROCEDURES: Firefighters should be equipped with self-contained breathing apparatus and turnout gear as a general precaution.

SECTION 6: REACTIVITY DATA

STABILITY: Stable HAZARDOUS POLYMERIZATION: Does not occur.
INCOMPATIBILITY (MATERIALS TO AVOID): Strong acids, oxidizing agents and excessive heat.
HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon, Nitrogen, Sulfur and other toxic gases.

SECTION 7: HEALTH HAZARD (ACUTE/CHRONIC)

CARCINOGENICITY: NTP: N IARC: N OSHA: N
EFFECTS OF OVEREXPOSURE:
EYES: May cause slight eye irritation, but does not injure eye tissue.

SKIN: Repeated or prolonged contact may irritate and cause dermatitis.

INHALATION: High vapor/aerosol concentrations (attainable at elevated temperatures well above ambient) are irritating to the eyes and respiratory tract, and may cause headaches, dizziness, anaesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death.

INGESTION: Minimal toxicity. Small amounts of this product aspirated into the respiratory system during ingestion or vomiting may cause mild to severe pulmonary injury, possibly progressing to death.

CHRONIC EFFECTS AND MEDICAL CONDITIONS: Repeated or prolonged occupational exposure may aggravate pre-existing skin and/or respiratory disorders.

SECTION 8: EMERGENCY AND FIRST AID

EYES: Flush with water for a minimum of 15 minutes. Consult a physician.
SKIN: Wash exposed area with soap and water. Remove contaminated clothing and wash before reuse. Consult a physician if irritation develops.
INHALATION: Remove to fresh air. If breathing is difficult consult a physician.
INGESTION: Call physician immediately. Only induce vomiting at the direction of a physician.

SECTION 9: PERSONAL PROTECTIVE MEASURES

EYE PROTECTION: Wear eye protection when chemical contact with eyes is possible. Contact lenses should not be worn.

PROTECTIVE GLOVES: When prolonged or repeated contact is possible, chemical resistant clothing (i.e. gloves) is recommended.
RESPIRATORY PROTECTION: Not required in most applications. Use NIOSH/MSHA approved respiratory protection if high concentrations of vapor or mist are generated.
VENTILATION: Either local exhaust or general room ventilation is recommended.
OTHER PROTECTIVE EQUIPMENT: Emergency eye wash station is recommended.

SECTION 10: SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Handle according to good manufacturing and warehousing practices. Wash hands before eating, drinking, smoking or using toilet facilities. Promptly remove contaminated clothing and wash before reuse. Store in original containers away from heat, sparks, open flames, strong acids or strong oxidizers.

SPILLS AND LEAKS: CAUTION: Floor may become slippery. Sweep/soak up small spills using inert material. For large spills, limit access to area. Dike and contain spill with inert material, if necessary, and transfer the material to containers suitable for recovery/disposal. Keep large spills out of sewers and open bodies of water.

WASTE DISPOSAL: Dispose of in accordance with all Federal, State and Local Environmental Laws in effect at the time.

Neither this data sheet nor any statement contained herein grants or extends any license, expressed or implied, in connection with patents issued or pending which maybe the property of the manufacturer or others. The information in this data sheet has been assembled by the manufacturer or his agent based on its own studies and on the work of others. Neither the manufacturer nor his agent makes any warranty, expressed or implied, as to the accuracy, completeness, or adequacy of the information contained herein. Neither the manufacturer nor his agent shall be held liable (regardless of fault) to the vendee, the vendee's employees or anyone for any direct, special or consequential damages arising out of or in connection with the accuracy, completeness, adequacy or furnishing of such information.

Data is supplied for use only in connection with occupational safety and health.